

# TECHNICAL DATA

## AUSTRALIAN CHEMICALS & COATINGS PTY LTD

ABN 92 884 104 142



69 Quantum Close,  
Dandenong South  
Vic 3175

Ph: (61 3) 9799 9833

Fax: (61 3) 9799 9033

NSW Ph: (61 2) 9737 9772

QLD Ph: (61 7) 3865 5787

Email: [sales@auschem.com.au](mailto:sales@auschem.com.au)

Website: [www.auschem.com.au](http://www.auschem.com.au)

THIS CHEMICAL IS  
FORMULATED FOR  
INDUSTRIAL USE ONLY

### WARNING

Contact with skin or clothing or other improper handling or use of this product may result in bodily harm or other damage. Before using or mixing the contents with other substances, all labels applied to container, the applicable Technical Data Sheet and Material Safety Data Sheet should be read and specific instructions and precautions followed to assure correct use and personal safety.

# ALKO-GEL 4366

## INTRODUCTION

ALKO-GEL 4366 is a white gel formulated for removal of alkyd and oil based paints. Application is by airless spraying or brushing. It is formulated to react with and dissolve the paint.

## APPLICATION

ALKO-GEL 4366 is supplied ready for use and can be sprayed using airless spray. Pressure should be kept low to avoid misting and special care should be taken not to allow overspray to contact any other painted surfaces.

Allow 30 minutes - 2 hours for the product to penetrate and react with the surface, then, high pressure rinse with fresh water. Some timbers will turn grey in colour after contact with ALKO-GEL 4366

## EQUIPMENT

Equipment should be made from mild or stainless steel. Aluminium should not be used as it will be attacked by ALKO-GEL 4366. PVC polyethylene and polypropylene are also suitable to use with ALKO-GEL 4366.

## TYPICAL PROPERTIES

TYPE	Thickened Potassium Hydroxide
APPEARANCE	White, slightly yellow gel
VISCOSITY	6,000 - 10,000 CPS - 25°C
COVERAGE	Varies according to paint thickness - generally ½ - 1 litre to M <sup>2</sup>

## SAFETY

Full protection should be worn while using ALKO-GEL 4366 including - coveralls, face shield and PVC gloves. Any spills on skin should be washed in fresh running water. Refer

Disclaimer: All statement, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any product defective at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct or consequential, arising out of the use of or inability to use the product. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in infringement of any patent rights and seller and manufacturer assume no responsibility or liability for any such infringement. We recommend prospective users determine the suitability of this product through independent testing before adopting on a commercial scale.