

TECHNICAL DATA

AUSTRALIAN CHEMICALS & COATINGS PTY LTD

ABN 92 884 104 142



69 Quantum Close,
Dandenong South
Vic 3175

Ph: (61 3) 9799 9833

Fax: (61 3) 9799 9033

NSW Ph: (61 2) 9737 9772

QLD Ph: (61 7) 3865 5787

Email: sales@auschem.com.au

Website: www.auschem.com.au

THIS CHEMICAL IS
FORMULATED FOR
INDUSTRIAL USE ONLY

WARNING

Contact with skin or clothing or other improper handling or use of this product may result in bodily harm or other damage. Before using or mixing the contents with other substances, all labels applied to container, the applicable Technical Data Sheet and Material Safety Data Sheet should be read and specific instructions and precautions followed to assure correct use and personal safety.

CARBYCLEAN

INTRODUCTION

CARBYCLEAN is a solvent based, inhibited de-carbonizer, degreaser, formulated for use on die cast aluminium and zinc substrates.

It will remove carbon, burnt on oil and strip most organic coatings.

SUMMARY OF OPERATING DATA

CARBYCLEAN is used as received, ideally in a closed mild steel tank to minimize evaporation.

Use at ambient temperature and add water to top of tank to improve the evaporation seal if required.

OPERATION RECOMMENDATIONS

- 1/ Pre-clean if oil excessive
- 2/ Immerse in CARBY CLEAN 5 mins – 4 hours
(at ambient temperature)
- 3/ Drain
- 4/ Rinse

EQUIPMENT

Mild steel or Stainless tank with close fitting lid

SAFETY

Do not work over open tank of CARBYCLEAN.
Store in a cool area away from direct sunlight
Refer MSDS for full details.

Disclaimer: All statement, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any product defective at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct or consequential, arising out of the use of or inability to use the product. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in infringement of any patent rights and seller and manufacturer assume no responsibility or liability for any such infringement. We recommend prospective users determine the suitability of this product through independent testing before adopting on a commercial scale.